

FIBRAPAN HIDROFUGO

by **FINSA**

The bar has been raised
with the highest standard in **quality.**

Excellent machining quality

Our unique manufacturing process ensures a stronger consistent bond in the core, for a clean cut and perfect for routing.



@blucarpentry



@freebirdinteriors

Superior paint finish

Obtain a better finish with less work. A denser board that requires less preparation time and less paint giving you an optimal finish.

Moisture Resistant MDF

Enhanced performance during cyclic test (EN 321, V313), with great results in both thickness swelling and internal bond.

Technical Data

UK STOCK
2440 x 1220
06 mm 09 mm
18 mm 22 mm
25 mm 30 mm

Properties	Units	Thickness mm				
		>4/6	>6/9	>9/12	>12/19	>19/30
DENSITY (*)	kg/m ³	855/830	825/770	765/745	745/730	730/715
INTERNAL BOND	N/mm ²	0.85	0.80	0.80	0.75	0.75
BENDING STRENGTH	N/mm ²	27	27	26	24	22
MODULUS OF ELASTICITY	N/mm ²	2700	2700	2500	2400	2300

*E1 classification: low formaldehyde content.

CLICK TO WATCH WHAT CUSTOMERS SAY ABOUT IT



@freebirdinteriors



@greenwichalcoveco



Get in touch to find your nearest stockist
T: 0151 651 2400 E: uk@finsa.com IG: @finsauk



FINSA